



The CS Leasing flat racks are designed for oversized or difficult loads that cannot be carried in a standard container.

Manufactured in steel with multiple lashing points, inward flush folding and full panelled end-walls, our flat racks provide strong, flexible and straightforward loading options - from the sides, ends, or above - allowing you to move plant, vehicles, machinery and other non-standard loads in marine and intermodal transport.

Key features

- Can be stored or backhauled in stacks:
 - Seven for 20ft
 - Four for 40ft
- Multiple loading options – sides, ends, above
- Flush folding end walls to form a platform
- Equipped with stake pockets and lashing bars
- Suitable for sling lifting from bottom corner castings
- Designed to carry out-of-gauge cargo

20ft Flat Rack

Typical Specification 20ft x 8ft x 8ft 6in

Dimensions*	Length	Ext 6,058mm Int 5,618mm
	Width	Ext 2,438mm Int 2,208mm
	Height	Ext 2,591mm Int 2,233mm
	Base height folded	370mm
	Stack height	folds 7 into 2,591mm (8ft 6in)
Rating	MGW	34,000kg 74,960bs
	Tare weight	2,790kg 6,150lbs
	Max payload	31,210kg 68,810lbs
	Concentrated load evenly distributed over centre 7.5 meters	20,000kg 44,106lbs

40ft Flat Rack

Typical Specification 40ft x 8ft x 8ft 6in

Dimensions*	Length	Ext 12,192mm Int 11,652mm
	Width	Ext 2,438mm Int 2,380mm
	Height	Ext 2,591mm Int 1,955mm
	Base height folded	648mm
	Stack height	folds 4 into 2,591mm (8ft 6in)
Rating	MGW	50,000kg 110,230lbs
	Tare weight	4,900kg 10,800lbs
	Max payload	45,100kg 99,430lbs
	Concentrated load evenly distributed over centre 2 meters	30,000kg 66,150lbs

*Dimensions are nominal and typical, there may be variations