



Compatible with all marine and intermodal transportation modes and designed for high density products that do not require large cubic capacities, CS Leasing BK2 certified half heights are licensed for the carriage of hazardous cargo in accordance with the International Maritime Dangerous Goods (IMDG) Code, making them popular within the mining and mineral export industries.

Available in various heights, depending on the product requirements, all units come with a removable lid addressing environmental concerns for controlling dust and loose products. Patent-protected designs are also available for the use with tippler discharge and lid lifter technology.

#### Key Features:

- Units can be connected two high and transported as one module
- Loading via fully removable lid or front door assembly
- BK2 and removable lid design to prevent leakages and protect the environment
- Internal epoxy anti-abrasion paint system
- Ergonomic side-mounted front hatch release handle, ensuring operator safety
- Top hinge hatch allows tip discharge
- Side hinge doors with swinging header for forklift truck access
- Full intermodal and container ship compatibility
- Most popular for mining and mineral export

### Half Height Bulk Container

#### Typical Specification 1.45m

Dimensions*	Length	Ext 6,058mm Int 5,836mm
	Width	Ext 2,438mm Int 2,132mm
	Height	Ext 1,450mm Int 1,214mm
Door opening	Width	2,284mm (top) 2,181mm (bottom)
	Height	1,023mm
Hatch opening	Width	2,284mm (top) 2,181mm (bottom)
	Height	1,008mm
	Header width	1,686mm
Roof opening	Length	5,702mm
	Width	2,132mm
Rating	Cubic capacity	15.5m <sup>3</sup> 549ft <sup>3</sup>
	MGW	35,000kg 77,160lbs
	Tare weight	3,150kg 6,940lbs
	Max payload	31,850kg 70,220lbs

\*Dimensions are nominal and typical, there may be variations

