



Insulated, uninsulated and baffled options available.

Stacking up to nine units high, our young fleet is equipped with 12m² effective surface of steam heating using Duplex stainless steel and ISO-required triple-closure secure design as standard.

Suitable for hazardous, non-hazardous and food grade cargoes, and with an easy-clean design, this fleet has been manufactured as a robust, economical solution for extended use.

- Uninsulated options available for 24,000 and 25,000 litre tanks.
- Baffled 26,000 litre tanks available with 3xV type fully welded stainless steel baffles, offering a large capacity tank with increased product flexibility.

Key Features:

- Handrail and full walkway options available
- Remote cable-operated airline release valve at ground level for operator safety
- Top outlet provision
- No cladding straps to minimise damage
- Approvals include: UIC, CSC, TIR, IM101, UK (DOT), RID/ADR, AAR600, FRA, TC, IMDG, US DOT
- Full intermodal compatibility
- Most popular for food, chemicals, petrochemicals and pharmaceuticals

Insulated, Uninsulated & Baffled

Typical Specification

20ft x 8ft x 8ft 6in ISO T11 Tank

Dimensions*	Length	Ext 6,058mm
	Width	Ext 2,438mm
	Height	Ext 2,591mm

26,000 litre Insulated Baffle Tank

Rating		
26,000 litre	MGW	36,000kg 79,365lbs
	Tare weight	3,790kg 8,455lb
	Max payload	32,210kg 71,010lb

*Dimensions are nominal and typical, there may be variations

